

## PRODUCT CARD

Short name

**DEC-W6X18ZN-(2000)**

Full name

Hidden deck fastener DECK-DRY screw UW6.0X18 (plank thickness min 21 mm) - galvanized silver

### BASE DATA

|               |                  |
|---------------|------------------|
| Product group | Deck-Dry         |
| Application   | • wooden decking |
| Code          | 301.020311       |

EAN



### TECHNICAL DATA

|                                   |                |
|-----------------------------------|----------------|
| Minimum height                    | 0 mm           |
| Maximum height                    | 0 mm           |
| Total dimension - length          | 8 mm           |
| Total dimension - width           | 8 mm           |
| Total product dimensions - height | 18 mm          |
| Head diameter (top plate)         | Ø 0 mm (0 cm2) |
| Base diameter                     | Ø 0 mm (0 cm2) |
| Weight                            | ~0 kg          |
| Wytrzymałość na obciążenia do     | 0 kg           |
| Fire resistance                   | E              |

|                                                                 |                                                     |
|-----------------------------------------------------------------|-----------------------------------------------------|
| Temperature range                                               | od -20°C do 65°C                                    |
| Color                                                           | silver                                              |
| Mandatory warranty                                              | Limited 10-year residential and commercial warranty |
| Country of origin                                               | Poland                                              |
| Material name                                                   | Galvanized steel                                    |
| Percentage of recycled material                                 | 0 %                                                 |
| Type of waste                                                   | • non-hazardous waste - recyclable                  |
| Project type                                                    | • exterior use                                      |
| What finishing materials can be used<br>• wooden decking boards |                                                     |

**Consists of**  
Screw 6x18 Zinc

## CERTIFICATES

Product certified by the Building Research Institute. NATIONAL TECHNICAL ASSESSMENT ITB-KOT-2022-2174



## LOGISTICS INFORMATION

| Package         | Quantity Packaging Value | Package weight | Empty package weight | Palett                       | Number of packages on a pallet | Number of pieces on a pallet | Pallet weight | Empty pallet weight |
|-----------------|--------------------------|----------------|----------------------|------------------------------|--------------------------------|------------------------------|---------------|---------------------|
| BOX 300x250x200 | 2000                     | 6 kg           | 0.24 kg              | WOODEN PALLET<br>120x100x220 | 160                            | 320000                       | 1016 kg       | 18 kg               |

## Characteristic features

Patented terrace installation system that increases the durability of decking boards

Features of the accessory:

1. Dedicated screw for mounting DECK-DRY connectors from the underside of the board
2. Made of galvanized steel
3. Minimum board thickness is 21 mm

## Application

Designed for raised deck terraces with wooden boards, where an elevated level of durability and resistance to rot is required.

Invisible board mounting from underneath - boards are not damaged by screws from the top.

Used for mounting DECK-DRY connectors to deck boards with a minimum thickness of 21 mm from the underside.

## Advantages

Advantages of the accessory:

1. Durability
2. Versatility of application

## Installation recommendations

Attach the connectors to the board. Drill holes for the Ø 6.0 mm screws in the board with a Ø 3.0 mm or Ø 3.5 mm drill bit (depending on the hardness of the wood) to a depth equal to the length of the screw minus 2 mm.

## Tools

P23 drill bits. Drill bit 6.0 mm.

## Recommendations for use

Do not use de-icing salt. Salt can cause corrosion of metal structural elements (screws, clips, adjustable feet) and damage surfaces adjacent to the terrace.